

TECHNICAL DATA SHEET

Biodegradable Asphalt Solvent

DESCRIPTION

SoySolv AR Plus is a heavy duty bio-based asphalt and tar remover, specifically formulated from renewable resources to replace diesel and citrus solvents. Through extensive research and field testing, SoySolv AR Plus is proven to be more efficient and safer than diesel or citrus based solvents for dissolving asphalt. AR Plus melts through inches of asphalt build-up, tack over spray, and asphalt seal coat. AR Plus is best for end of shift clean up or pre-maintenance cleaning.

KEY BENEFITS

- Economical Pricing Lower cost than dlimonene based products
- Heavy Duty cleaning power removes the toughest build-up - including Trackless Tack and Ultrafuse
- Slow Evaporation Rate Leaves behind slick film preventing future build-up
- 100% Biodegradable
- Safe and easy to use, non-toxic formulation
- Lab and field tested to outperform diesel and last longer than citrus

USAGE DIRECTIONS

- DO NOT DILUTE
- TO REMOVE ASPHALT BUILDUP: Coat tools or equipment to be cleaned with SoySolv AR Plus, then wait 5-10 minutes for AR Plus to penetrate the asphalt. For heavy buildup, allow for longer time. SoySolv AR Plus has a low evaporation rate and will continue working even after several hours post application. Use scraper or high water pressure to remove softened asphalt.
- IF SPILLED ON FRESH MAT: Flush grea immediately with water to deactivate solvency. SoySolv AR Plus will not harm or degrade asphalt once rinsed.

TECHNICAL DATA

APPEARANCE	Amber
WEIGHT	7.3 lbs. per gallon
FLASH POINT	<u>></u> 141° F
SHELF LIFE	12 months properly stored
GHS HAZARDS	See Safety Data Sheet
ECOTOXICITY	100% Biodegradable
FREEZE POINT	> 20°F
WATER SOLUBILITY	Emulsifiable
ODOR	Citrus

PRECAUTIONS

- Wear protective gloves/protective clothing/eye protection. Use PPE as required per Safety Data Sheet
- Read and understand the Safety Data Sheet before each use
- Product should be stored above 40° F and below 120° F. Protect from freezing. Store in tightly sealed, full containers.
- Warning: to help prevent damage to painted surfaces, wipe off and/or rinse with water
- Product may expand during storage causing pressure to build-up. Open container carefully.
- Additional precautions, safety information and first aid are contained in the SDS

